



Dually wheel规格表

序号	SIZE	TYPE	Inset (mm)	outset(m m)	PCD HOLES	P. C. D (mm)	Stud (mm)	C. B (mm)	MAX LOAD	MAX LOAD	WERGHT (kg) 参考	VALVE	ROUGH weight
1	22*8.25	前轮	145	167	8	165	16-28.575-60°	121.4	1589	3500	19.56	TR413, TR544D/554D	48.2
2		后外轮	145	167	8	165	16-28.575-60°	121.4	1589	3500	19.55	TR413, TR544D/554D	48.2
3		后内轮	145	167	8	165	16	121.4	1589	3500	19.93	TR413, TR544D/554D	48.2
4		前轮	145	167	8	200	16-28.575-60°	142.1	1589	3500	19.31	TR413, TR544D/554D	48.2
5		后外轮	145	167	8	200	16-28.575-60°	142.1	1589	3500	19.29	TR413, TR544D/554D	48.2
6		后内轮	145	167	8	200	16	142.1	1589	3500	19.67	TR413, TR544D/554D	48.2
7		前轮	145	167	8	210	16-28.575-60°	154.3	1589	3500	19.13	TR413, TR544D/554D	48.2
8		后外轮	145	167	8	210	16-28.575-60°	154.3	1589	3500	19.12	TR413, TR544D/554D	48.2
9		后内轮	145	167	8	210	16	154.3	1589	3500	19.49	TR413, TR544D/554D	48.2
10	24*8.25	前轮	146	168	8	165.1	16-29-60°	121.3	1270	2800	22.23	TR544D/554D	51
11		后外轮	146	168	8	165.1	16-29-60°	121.3	1270	2800	22.23	TR544D/554D	51
12		后内轮	146	163	8	165.1	16	121.3	1270	2800	21.22	TR544D/554D	51
13		前轮	146	168	8	200	16-29-60°	142	1270	2800	22.23	TR544D/554D	51
14		后外轮	146	168	8	200	16-29-60°	142	1270	2800	22.23	TR544D/554D	51
15		后内轮	146	163	8	200	16	142	1270	2800	21.22	TR544D/554D	51
16		前轮	146	168	8	210	16-29-60°	154.2	1270	2800	22.23	TR544D/554D	51
17		后外轮	146	168	8	210	16-29-60°	154.2	1270	2800	22.23	TR544D/554D	51
18		后内轮	146	163	8	210	16	154.2	1270	2800	21.22	TR544D/554D	51
19	26*8.25	前轮	132	156	8	165.1	16-29-60°	121.3	1270	2800	21.36	TR413, TR544/554	59
20		后外轮	132	156	8	165.1	16-29-60°	121.3	1270	2800	21.36	TR413, TR544/554	59
21		后内轮	132	149.5	8	165.1	16	121.3	1270	2800	20.15	TR413, TR544/554	59
22		前轮	132	156	8	200	16-29-60°	142	1270	2800	21.36	TR413, TR544/554	59
23		后外轮	132	156	8	200	16-29-60°	142	1270	2800	21.36	TR413, TR544/554	59
24		后内轮	132	149.5	8	200	16	142	1270	2800	20.15	TR413, TR544/554	59
25		前轮	132	156	8	210	16-29-60°	154.2	1270	2800	21.36	TR413, TR544/554	59
26		后外轮	132	156	8	210	16-29-60°	154.2	1270	2800	21.36	TR413, TR544/554	59
27		后内轮	132	149.5	8	210	16	154.2	1270	2800	20.15	TR413, TR544/554	59
28	26*8.25	/	146	168	/	/	/	121.3	/	/	/	模具开发中	

注：中心孔尺寸类似，小数点后的数值不同（因不同客户需求不同）